Telefon: 02173-2027007
Email: info@net4web.de

Albrecht-Dürer-Str. 6
D-40764 Langenfeld

AMASS® XT-60BE-F Buchse und XT-60H mit Schutzkappen für Gehäusemontage inkl. Schrauben u. Muttern



Marke: Amass®
Produktcode: 0711906114462
Verfügbar: 20

Preis: 3,99€

Ohne Steuer: 3,35€

Kurzbeschreibung

Originalware von AMASS® für den Hochstrombetrieb im Modellbau. / Original product from AMASS® for high-current operation in model making.

Beschreibung

Die XT-60 Steckverbinder von Amass® sind für den Hochstromeinsatz vor allem im Modellbau ausgelegt. Mit den Steckverbindern können z.B. sichere und stabile Akku-Anschlüsse in Gehäusen realisiert werden. Das macht den Umgang mit Lipos ein Stückchen sicherer. Die Einbaubuchse XT-60BE-F kann durch die mitgelieferte Schutzkappe bei Nichtverwendung geschützt werden. Für den XT-60H Stecker liegt ebenfalls eine Schutzkappe bei. Bei Verwendung der Schutzkappe brauchen Sie die Lötstellen nicht mit Schrumpfschlauch zu isolieren. Gleichzeitig dient die Schutzkappe auch als Knickschutz und verhindert so zuverlässig das Brechen von Lötstellen und Kabeln. Die Schutzkappe rastet sicher und stabil am Stecker ein. Es muss also nichts geklebt werden.

Zwei passende Schrauben und Muttern gehören bereits zum Lieferumfang. Die

Schrauben können vollständig eingedreht werden. Die Schraubenköpfe stoßen also nicht an. Die genauen Maße entnehmen Sie bitte den Fotos.

AMASS® ist bekannt als Hersteller sehr hochwertiger Steckverbinder.

Lieferumfang:

1 Stück XT-60BE-F Einbaubuchse (vergoldete Kontakte) mit Lötanschluss

1 Stück Schutzkappe für XT-60BE-F

1 Stück XT-60H Stecker (vergoldete Kontakte) mit Lötanschluss

1 Stück Schutzkappe für XT-60H

2 Stück Senkkopfschrauben

2 Stück Muttern

Technische Daten:

Lochabstand: 25,4mm

Setgewicht: ca. 15g

Farbe/Material: orangefarbenes PA-Nylon

Kontakte: Kupferkern, vergoldet

RoHS-Konform: Ja

Kontaktwiderstand: 0,4m?

Isolationswiderstand: 2000M?

Flammfestigkeit: UL94 V0

Nennspannung: max. DC 500V

Nennstrom: max. 30A

Spitzenstrom: max. 60A für 1 Minute

Steckzyklen: 1000mal

Empf. Löttemperatur: ~480°C

Lagertemperatur: -20°C bis +120°C

Alle angegebenen Maße sind Circa-Maße und können geringfügig abweichen.

WEEE-Registrierungsnummer: DE33880481

English

The XT-60 connectors from Amass® are designed for high-current use, especially in model making. The connectors can be used to create safe and stable battery connections in housings, for example. This makes handling LiPos a little safer. The XT-60BE-F built-in socket can be protected with the protective cap provided when not in use. A protective cap is also included for the XT-60H connector. When using the protective cap, you do not need to insulate the soldering points with shrink tubing. At the same time, the protective cap also serves as a kink protection and thus reliably prevents soldering points and cables from breaking. The protective cap snaps securely and stably into the connector. So nothing needs to be glued.

Two matching screws and nuts are already included in the delivery. The screws can be screwed in completely. The screw heads do not touch. Please refer to the photos for the exact dimensions.

AMASS® is known as a manufacturer of very high-quality connectors.

Scope of delivery:

1 piece XT-60BE-F built-in socket (gold-plated contacts) with solder connection

1 piece protective cap for XT-60BE-F

1 piece XT-60H plug (gold-plated contacts) with solder connection

1 piece protective cap for XT-60H

2 pieces countersunk screws

2 pieces nuts

Technical data:

Hole spacing: 25.4mm

Set weight: approx. 15g

Color/material: orange PA nylon

Contacts: copper core, gold-plated

RoHS compliant: Yes

Contact resistance: 0.4m?

Insulation resistance: 2000M?

Flame resistance: UL94 V0

Nominal voltage: max. DC 500V

Nominal current: max. 30A

Peak current: max. 60A for 1 minute

Plug-in cycles: 1000 times

Recommended soldering temperature: ~480°C

Storage temperature: -20°C to +120°C

All dimensions given are approximate and may vary slightly.

WEEE registration number: DE33880481

Produkt Gallerie









